

# HYUNDAI

8MP Outdoor Fixed Dome IP

# 8MP

## H.265 Dome Camera, Pro IP with Fixed Lens

Model: HY-VP525V-F

8MP

H.265

WDR

POE

Onvif

### Features:

- 8MP Pro IP Dome Camera
- 1/2.8" SONY Stravis Back-illuminated CMOS sensor
- H.264/H.264+/H.265/H.265+ Compression Method
- 3.6mm Fixed Lens
- IR Distance 25m Max.
- IP67 Outdoor Metal Case
- Support built-in POE
- Support 3D digital noise reduction, support WDR
- Support automatic electronic shutter function to adapt to different monitoring environments
- Support ONVIF, SLINK protocol



### Dimensions:



## Specifications:

Model NO.	HY-VP525V-F
<b>Camera</b>	
Image Sensor	1/2.7" SmartSens CMOS sensor
Resolution	8MP
Effective Pixels	3872(H)*2180(V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/30-1/10000Sec
Minimum Illumination	0.01Lux
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network
Reset Button	Optional
<b>Lens</b>	
Focus Length	2.8mm
Focus Control	Fixed
Lens Type	Fixed
Pixels	8MP
<b>Night Vision</b>	
Infrared LED	42μ x 2PCS
Infrared Distance	25M
IR Status	Auto Control
IR Power On	Manual & Timed mode
<b>Network</b>	
Ethernet	RJ-45 (10/100Base-T)
Wireless	/
Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, UDP
ONVIF	Support ONVIF 2.4(Profile S/T/G)
P2P	YES, Support QR Code
POE	Internal, Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
Main Stream 1	3840*2160@20fps
Main Stream 2	2592*1536@20fps 2560*1440@20fps
Main Stream 3	1920*1080@20fps 1280*720@20fps
Sub Stream 1	1280*720@20fps
Sub Stream 2	720*480@20fps

# HYUNDAI

8MP Outdoor Fixed Dome IP

<b>Sub Stream 3</b>	/
<b>Tri Stream</b>	1280*720@20fps 720*480@20fps
<b>IE Brower</b>	IE8-11, Google Chrome, Firefox , Mac Safari
<b>Smart Phone</b>	iPhone, Android
<b>AI Function</b>	
<b>Intelligent Analysis</b>	/
<b>Camera Features</b>	
<b>Day/Night</b>	Color/ B&W (IR-CUT )
<b>Image Config</b>	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control), Video Tampering, HLC, Distortion
<b>Full Color</b>	/
<b>Corridor Pattern</b>	Support
<b>Defog Mode</b>	Support
<b>ROI</b>	Support
<b>BLC</b>	Support
<b>WDR</b>	HDR: 120dB
<b>Motion Detection</b>	Support
<b>Privacy Masking</b>	3 Rectangular Zone
<b>Recording Mode</b>	NVR/CMS/Web
<b>Language</b>	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Arabic, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Nederlands, Czech, Vietnamese
<b>Interface</b>	
<b>Audio</b>	Built-in MIC
<b>Alarm</b>	/
<b>SD Card Slot</b>	Internal, Support Max 512GB
<b>RS485</b>	/
<b>General</b>	
<b>Housing</b>	Metal , IP67
<b>Anti-cut Bracket</b>	Optional Wall Bracket
<b>IR Cut Filter</b>	YES
<b>Operation Temperature</b>	-20°C ~ +60°C RH95% Max
<b>Storage Temperature</b>	-20°C ~ +60°C RH95% Max
<b>Power Source</b>	DC12V±10%, 700mA
<b>Dimension</b>	∅ 109 x 93(H) mm
<b>Weight</b>	600g